

Fiber Mulch

Paper Fiber Mulch

- 1 Paper fiber mulch is derived from 100% quality recycled newspaper, kraft paper, cardboard, paper mill sludge, and other grades of pre and post consumer waste paper.
- 2 Flocculating tackifier increases yield-so every bag goes further providing greater loft within the matrix and outstanding erosion control performance.
- 3 It is free of extraneous foreign material such as metals, plastic, and glass that will adversely affect the service quality of the hydraulic applied fiber mulch.
- 4 It is hydraulically applied within a water slurry to the soil surface from a hose or tower nozzle.
- 5 It provides a protective cover for germination and growth as well as soil stabilization at the speed germination zone.



Handling and Storage

Protect damage from weather, excessive temperatures and construction operations. Keeping dry is recommended.

Test Data

Water-Holding Capacity : 930% min.
Moisture Content : 14.80%
Organic Content : 99.6%
Ash Content : 0.76
pH Range : 7.2

Suggested Application Rates

Condition	Rate
Modest to 4 : 1 Slope.....	200 lbs./acre
3:1 Slope	2650 lbs./acre
3:1 to 2:1 Slope	3250 lbs./acre



TOYO GREENLAND CO., LTD.

東陽綠化有限公司

No.58, South Section, Wah Shan Village, Sheung Shui, N.T., Hong Kong.

Tel: (852) 2639 9312 Fax: (852) 2377 2150

Web-site: <http://www.toyogreen.com> E-mail: enquiry@toyogreen.com



Lastest Version: 20 September 2006